

Package ‘robRatio’

September 17, 2025

Type Package

Title M-Estimators for Generalized Ratio and Linear Regression Models

Version 0.1.0

Author Kazumi Wada [aut, cre] (ORCID: <<https://orcid.org/0000-0002-9578-1588>>)

Maintainer Kazumi Wada <kazwd2008@gmail.com>

Description Robust estimators for generalized ratio model (Wada, Sakashita and Tsubaki, 2021)<[doi:10.17713/ajs.v50i1.994](https://doi.org/10.17713/ajs.v50i1.994)> and linear regression model by the IRLS(Iterative reweighted least squares) algorithm are contained.

License GPL (>= 3)

URL <<https://github.com/kazwd2008/robRatio>>

Encoding UTF-8

RoxygenNote 7.3.2

Depends stats

Suggests knitr, MASS, rmarkdown, testthat (>= 3.0.0), latex2exp,
RColorBrewer

Config/testthat.edition 3

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2025-09-17 10:20:02 UTC

Contents

Hirls.aad	2
Hirls.mad	3
robGR	4
robRatio	5
robReg	7
RrH.aad	8
RrH.mad	9

RrT.aad	10
RrT.mad	11
Tirls.aad	12
Tirls.mad	12

Index**14**

Hirls.aad	<i>Robust estimator for the linear regression model with Huber's weight function and AAD scal by iteratively re-weighted least squares (IRLS) algorithm</i>
------------------	---

Description

Robust estimator for the linear regression model with Huber's weight function and AAD scal by iteratively re-weighted least squares (IRLS) algorithm

Usage

```
Hirls.aad(
  x1,
  y1,
  rt = rep(1, length(y1)),
  c1 = 1.15,
  rp.max = 150,
  cg.rt = 0.01
)
```

Arguments

x1	explanatory variable(s)
y1	objective variable
rt	sample weights
c1	tuning parameter from 1.15 to 2.30 for the scale parameter of AAD(Average Absolute Deviation)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

- HB results of robust regression
- wt robust weights
- rp total number of iteration
- s1 changes in scale through iterative calculation

Hirls.mad	<i>Robust estimator for the linear regression model with Huber's weight function and MAD scal by iteratively re-weighted least squares (IRLS) algorithm</i>
-----------	---

Description

Robust estimator for the linear regression model with Huber's weight function and MAD scal by iteratively re-weighted least squares (IRLS) algorithm

Usage

```
Hirls.mad(
  x1,
  y1,
  rt = rep(1, length(y1)),
  c1 = 1.44,
  rp.max = 150,
  cg.rt = 0.01
)
```

Arguments

x1	explanatory variable(s)
y1	objective variable
rt	sample weights
c1	tuning parameter from 1.44 to 2.88 for the scale parameter of MAD(Median Absolute Deviation)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

- HB results of robust regression
- wt robust weights
- rp total number of iteration
- s1 changes in scale through iterative calculation

robGR

*Robust estimator for a generalized ratio model***Description**

This function simultaneously estimates two parameters of the generalized ratio model [doi:10.17713/ajs.v50i1.994](#). It uses Tukey's biweight function and AAD for scale of quasi residuals.

This robGR function simultaneously estimate two parameters of the generalized ratio model. It uses Tukey's biweight function and AAD for scale of quasi residuals.

Usage

```
robGR(x1, y1, g1 = 0, c1 = 8, rp.max = 100, cg.rt = 0.001)
```

```
robGR(x1, y1, g1 = 0, c1 = 8, rp.max = 100, cg.rt = 0.001)
```

Arguments

x1	single explanatory variable (a vector)
y1	objective variable to be imputed (a vector)
g1	initial gamma value (default g1=0.5)
c1	tuning constant for Tukey's biweight function. Supposed to choose 4 to 8. Smaller figure is more robust (default tp=8).
rp.max	maximum number of iteration (default: rp.max=50)
cg.rt	convergence condition to stop iteration (default: cg.rt=0.001)

Value

a list with the following elements

par	robustly estimated ratio of y1 to x1 (beta)
g1	robustly estimated power (gamma)
res	homoscedastic quasi-residuals
wt	robust weights
rp	total number of iteration
efg	error flag. 1: calculation not covered, 0: successful termination
rt.cg	change of par(beta)
g1.cg	changes of g1(gamma)
s1.cg	changes of the scale(AAD)
a list with the following elements	
par	robustly estimated ratio of y1 to x1 (beta)
g1	robustly estimated power (gamma)

```

res homoscedastic quasi-residuals
wt robust weights
rp total number of iteration
efg error flag. 1: calculation not covered, 0: successful termination
rt.cg change of par(beta)
g1.cg changes of g1(gamma)
s1.cg changes of the scale(AAD)

```

robRatio*Robust estimator for ratio models***Description**

This function integrates 4 functions (RrT.aad, RrT.mad, RrH.aad and RrH.mad) for estimating generalized ratio model. Please note that the values for the tuning parameter tp allowed in this function is standardized. See the vignette for the detail.

Usage

```

robRatio(
  x1,
  y1,
  gm = "b",
  wf = "T",
  scale = "AAD",
  rt = 1,
  tp = 8,
  rp.max = 100,
  cg.rt = 0.01
)

```

Arguments

x1	single explanatory variable (a vector)
y1	objective variable to be imputed (a vector)
gm	indication of gamma value as follows: gm="a": gamma=1 gm="b": gamma=1/2 (conventional ratio model) gm="c": gamma=0 (regression model without intercept)
wf	weight function (wf=T : Tukey, wf=H : Huber)
scale	scale for residuals. "AAD"(default) or "MAD".
rt	sample weight (default 1)

tp	standardized tuning parameter. choose 4, 6 or 8. Smaller figure is more robust (default tp=8). See details.
rp.max	maximum number of iteration (default: rp.max=50)
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

cond Weight function, scale, and other arguments choosed
par robustly estimated ratio of y1 to x1 (beta)
res homoscedastic quasi-residuals
wt robust weights
rp total number of iteration
s1 changes of the scale (AAD or MAD)
efg error flag. 1: acalculia (all weights become zero) 0: successful termination

Examples

```
require(robRatio)

x1 <- seq(1, 10, by=0.1)
#e <- rnorm(length(x1))
e <- rt(length(x1), df=3) # error term following t distribution

b <- 2 # true value of slope

y1 <- b*x1 + x1*e # example 1: gamma=1
y2 <- b*x1 + sqrt(x1)*e # example 2: gamma=1/2

o1 <- robRatio(x1, y1, gm="a")
o2 <- robRatio(x1, y2, gm="b")

o1$par; o2$par # estimated slope

cols = RColorBrewer::brewer.pal(11, "PiYG")
cl1 <- round((o1$wt)*10+1)
cl2 <- round((o2$wt)*10+1)

oldpar <- par(mfrow=c(1,2))
plot(x1, y1, col=cols[cl1], pch=20)
plot(x1, y2, col=cols[cl2], pch=20)
par(oldpar)
```

<code>robReg</code>	<i>[Robust estimator for regression models]</i>
---------------------	---

Description

This function is for Robust regression by the IRLS algorithm. It integrates child functions contained in Tirls.r and Hirls.r.

Usage

```
robReg(
  x1,
  y1,
  wf = "T",
  scale = "AAD",
  rt = rep(1, length(y1)),
  tp = 8,
  rp.max = 150,
  cg.rt = 0.01
)
```

Arguments

<code>x1</code>	explanatory variable in regression (a vector or a matrix)
<code>y1</code>	objective variable in regression (a vector)
<code>wf</code>	weight function ("T" for Tukey's biweight, and "H" for Huber weight)
<code>scale</code>	scale for residuals. "AAD"(default) or "MAD".
<code>rt</code>	sample weight (default 1)
<code>tp</code>	tuning parameter (tp=4, 6 or 8) for weight function. Smaller figure is more robust.
<code>rp.max</code>	The maximum number of iteration (default 150)
<code>cg.rt</code>	convergence condition to stop iteration (default: cg.rt=0.001)

Value

a list with the following elements

- `cond` Weight function, scale, and other arguments choosed
- `TK` robustly estimated regression coefficients using Tukey's biweight
- `HB` robustly estimated regression coefficients using Huber weight
- `wt` final robust weights
- `rp` total number of iteration
- `s1` iterative changes in the sclae of residuals (AAD or MAD)

Examples

```

require(robRatio)

set.seed(4)
cov1 <- matrix(c(3, 2.8, 2.8, 3), 2, 2)
cov2 <- matrix(c(2.5, 0, 0, 3), 2, 2)
dat1 <- MASS::mvrnorm(n=400, mu=c(100, 100), Sigma=cov1, empirical=TRUE)
dat2 <- cbind(runif(100, min=96, max=104), runif(50, min=95, max=105))
dat3 <- matrix(c(103, 103.5, 104.5, 104.8, 96, 98, 94, 95), 4, 2)
dat <- rbind(dat1, dat2, dat3)
plot(dat)
y1 <- dat[,2]
x1 <- dat[,1]

R0 <- lm(y1~x1)           # regression by OLS

o1 <- robReg(x1, y1, tp=4) # robust regression by IRLS (more robust)
o2 <- robReg(x1, y1, tp=8) # robust regression by IRLS (less robust)

oldpar <- par(mfrow=c(2,2))

# non-robust regression
plot(dat, pch=20, main="non-robust regression")
abline(R0, col="red", lwd=2)

# robust regression with coloring robust weight
f.o1 <- rep(1, length(x1))
f.o1[which(o1$wt < 0.8)] <- 3
f.o1[which(o1$wt < 0.5)] <- 7
f.o1[which(o1$wt < 0.2)] <- 2
f.o1[which(o1$wt == 0)] <- 8

plot(x1, y1, pch=20, col=f.o1)
abline(R0, col="red", lty=3)
abline(o1$TK, col="blue", lwd=2)
abline(o2$TK, col="cyan", lwd=2)

# robust weights (more robust)
hist(o1$wt, main="tp=4(more robust)")

# robust weights (less robust)
hist(o2$wt, main="tp=4(less robust)")

par(oldpar)

```

Description

Robust estimator for a generalized ratio model with Huber's weight function and AAD scal by iteratively re-weighted least squares (IRLS) algorithm for M-estimation

Usage

```
RrH.aad(x1, y1, g1 = 0.5, c1 = 2.3, rp.max = 100, cg.rt = 0.01)
```

Arguments

x1	single explanatory variable
y1	objective variable
g1	power (default: g1=0.5(conventional ratio model))
c1	tuning parameter usually from 1.15 to 2.30 (smaller figure is more robust)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

par	robustly estimated ratio of y1 to x1
res	homoscedastic quasi-residuals
wt	robust weights
rp	total number of iteration
s1	changes in scale through iterative calculation
efg	error flag. 1: acalculia (all weights become zero) 0: successful termination

RrH.mad

Robust estimator for a generalized ratio model with Huber's weight function and MAD scal by iteratively re-weighted least squares (IRLS) algorithm for M-estimation

Description

Robust estimator for a generalized ratio model with Huber's weight function and MAD scal by iteratively re-weighted least squares (IRLS) algorithm for M-estimation

Usage

```
RrH.mad(x1, y1, g1 = 0.5, c1 = 2.88, rp.max = 100, cg.rt = 0.01)
```

Arguments

x1	single explanatory variable
y1	objective variable
g1	power (default: g1=0.5(conventional ratio model))
c1	tuning parameter usually from 1.44 to 2.88 (equivalent to those for AAD scale)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

par	robustly estimated ratio of y1 to x1
res	homoscedastic quasi-residuals
wt	robust weights
rp	total number of iteration
s1	changes in scale through iterative calculation
efg	error flag. 1: acalculia (all weights become zero) 0: successful termination

RrT.aad

Robust estimator for a generalized ratio model with Tukey biweight function and AAD scale by iteratively re-weighted least squares (IRLS) algorithm for M-estimation

Description

Robust estimator for a generalized ratio model with Tukey biweight function and AAD scale by iteratively re-weighted least squares (IRLS) algorithm for M-estimation

Usage

```
RrT.aad(x1, y1, g1 = 0.5, c1 = 8, rp.max = 100, cg.rt = 0.01)
```

Arguments

x1	single explanatory variable
y1	objective variable
g1	power (default: g1=0.5(conventional ratio model))
c1	tuning parameter usually from 4 to 8 (smaller figure is more robust)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

par	robustly estimated ratio of y1 to x1
res	homoscedastic quasi-residuals
wt	robust weights
rp	total number of iteration
s1	changes in scale through iterative calculation
efg	error flag. 1: acalculia (all weights become zero) 0: successful termination

RrT.mad

Robust estimator for a generalized ratio model with Tukey biweight function and MAD scale by iteratively re-weighted least squares (IRLS) algorithm for M-estimation

Description

Robust estimator for a generalized ratio model with Tukey biweight function and MAD scale by iteratively re-weighted least squares (IRLS) algorithm for M-estimation

Usage

```
RrT.mad(x1, y1, g1 = 0.5, c1 = 10.03, rp.max = 100, cg.rt = 0.01)
```

Arguments

x1	single explanatory variable
y1	objective variable
g1	power (default: g1=0.5(conventional ratio model))
c1	tuning parameter usually from 5.01 to 10.03 (equivalent to those for AAD scale)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

par	robustly estimated ratio of y1 to x1
res	homoscedastic quasi-residuals
wt	robust weights
rp	total number of iteration
s1	changes of the scale (AAD or MAD)
efg	error flag. 1: acalculia (all weights become zero) 0: successful termination

Tirls.aad

Robust estimator for the linear regression model with Tukey's biweight function and AAD scale by iteratively re-weighted least squares (IRLS) algorithm

Description

Robust estimator for the linear regression model with Tukey's biweight function and AAD scale by iteratively re-weighted least squares (IRLS) algorithm

Usage

```
Tirls.aad(x1, y1, rt = rep(1, length(y1)), c1 = 8, rp.max = 150, cg.rt = 0.01)
```

Arguments

x1	explanatory variable(s)
y1	objective variable
rt	sample weights
c1	tuning parameter from 4 to 8 for the scale parameter of AAD(Average Absolute Deviation)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

a list with the following elements

- TK results of robust regression
- wt robust weights
- rp total number of iteration
- s1 changes in scale through iterative calculation

Tirls.mad

Robust estimator for the linear regression model with Tukey's biweight function and MAD scale by iteratively re-weighted least squares (IRLS) algorithm

Description

Robust estimator for the linear regression model with Tukey's biweight function and MAD scale by iteratively re-weighted least squares (IRLS) algorithm

Usage

```
Tirls.mad(  
  x1,  
  y1,  
  rt = rep(1, length(y1)),  
  c1 = 10.03,  
  rp.max = 150,  
  cg.rt = 0.01  
)
```

Arguments

x1	explanatory variable(s)
y1	objective variable
rt	sample weights
c1	tuning parameter from 5.01 to 10.03 for the scale parameter of MAD(Median Absolute Deviation)
rp.max	maximum number of iteration
cg.rt	convergence condition to stop iteration (default: cg1=0.001)

Value

- a list with the following elements
 - TK results of robust regression
 - wt robust weights
 - rp total number of iteration
 - s1 changes in scale through iterative calculation

Index

Hirls.aad, [2](#)

Hirls.mad, [3](#)

robGR, [4](#)

robRatio, [5](#)

robReg, [7](#)

RrH.aad, [8](#)

RrH.mad, [9](#)

RrT.aad, [10](#)

RrT.mad, [11](#)

Tirls.aad, [12](#)

Tirls.mad, [12](#)