

ZyXEL ES-2024PWR V3.70(All.0)C1

Release Note/Manual Supplement

Date: Nov. 27, 2006

This document describes the features in the ES-2024PWR product for its 3.70(All.0)C1 release.

Support Platforms:

ZyXEL ES-2024PWR V3.70(All.0)C1 supports models: ZyXEL ES-2024PWR

Version:

OS Version: V3.70(All.0) | 08/01/2006

BootBase Version: V1.01 | 11/27/2006

Default Bootbase Setting:

ZyNOS Version	V3.70(All.0) 08/01/2006 19:03:02
Bootbase Version	V1.01 11/27/2006 14:04:59
Vendor Name	ZyXEL
Product Model	ES-2024PWR
ZyNOS Code Model	
HTP Code Model	Unknown
ZyNOS ROM address	bfc10000
System Type	8
MAC Address	0019CB000001
Default Country Code	FF
Boot Module Debug Flag	01
RomFile Version	3D
RomFile Checksum	936c
ZyNOS Checksum	8012
SNMP MIB level & OID	060102030405060708091011121314151617181920
Main Feature Bits	C0
Other Feature Bits	
01 10 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00-00 00 13 00 00 00	

Enhanced Features:

None

Known Issue:

1. For the same ports, LACP and RSTP cannot be activated at the same time
2. The counter of packets whose length is between 1519 and 1522 (without VLAN tag but including FCS) will be counted both in the range of 1024 to 1518 and Giant.

Bug Fix:

None

Limitation of Settings:

1. VLAN 1Q static entry 256
2. Static MAC forwarding entry 256
3. MAC filtering entry 256
4. Cluster member 24
5. Management IP address 64
6. IGMP MVR entry 256
7. IGMP Filtering profile 256
8. Syslog server entry 4

Change History:

V3.70(All.0)C1 (11/27/2006)
Change the prefix of MAC address

V3.70(All.0) (07/31/2006)
First Public Version

ZyXEL ES-2024PWR V3.70(All.0)C0

Release Note/Manual Supplement

Date: Aug 1, 2006

This document describes the features in the ES-2024PWR product for its 3.70(All.0)C0 release.

Support Platforms:

ZyXEL ES-2024PWR V3.70(All.0)C0 supports models: ZyXEL ES-2024PWR

Version:

OS Version: V3.70(All.0) | 08/01/2006
BootBase Version: V1.0 | 07/07/2006

Default Bootbase Setting:

ZyNOS Version	V3.70(All.0) 08/01/2006 19:03:02
Bootbase Version	V1.0 07/07/2006 16:49:24
Vendor Name	ZyXEL
Product Model	ES-2024PWR
ZyNOS Code Model	
HTP Code Model	Unknown
ZyNOS ROM address	bfc10000
System Type	8
MAC Address	001349000001
Default Country Code	FF
Boot Module Debug Flag	01
RomFile Version	3D
RomFile Checksum	936c
ZyNOS Checksum	8012
SNMP MIB level & OID	060102030405060708091011121314151617181920
Main Feature Bits	C0
Other Feature Bits	
01 10 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00-00 00 13 00 00 00	

Features:

1. MAC address learning
2. Support IEEE 802.1D transparent bridge
3. Support IEEE 802.1Q tagged VLAN
4. Support Port-based VLAN
5. Support IEEE 802.1X
6. Support IEEE 802.1W
7. Support IEEE 802.3AD
8. Support GVRP
9. IGMP snooping
10. Support IEEE 802.1p

11. Automatic age out
12. Specific MAC addresses forwarding per port
13. MAC Filtering
14. Port Trunking
15. Port Mirroring
16. Bandwidth Control
17. Broadcast Storm Control
18. Support Strict Priority and WRR queuing method
19. Static IP management or dynamic IP(DHCP client)
20. Multiple IP address management
21. Firmware upgrade and configuration backup/restore.
22. Remote manageable.
23. Cluster Management
24. WEB manageable
25. Support RFC-1213 MIB II
26. Support RFC-1493 Bridge MIB
27. Support RFC-1643 Ethernet MIB
28. Support RFC-1757 Four group of RMON
29. Support RFC-2674 VLAN MIB
30. NEW CLI supported
31. System configuration backup / restore in text-mode
32. Multiple login supported
33. Radius management authentication
34. SSH/SSL support
35. DiffServ feature (DSCP – 802.1p priority mapping)
36. Multicast
37. MVR
38. IGMP Filtering
39. Syslog
40. Administration user management
41. RADIUS enhancement(for 802.1X enhancement and multiple radius servers)
42. IGMP enhancement
43. Web enhancement (Select all, Clone)
44. Support IEEE 802.3af
45. Support RFC-3621 Power Ethernet MIB

Known Issue:

3. For the same ports, LACP and RSTP cannot be activated at the same time
4. The counter of packets whose length is between 1519 and 1522 (without VLAN tag but including FCS) will be counted both in the range of 1024 to 1518 and Giant.

Limitation of Settings:

9. VLAN 1Q static entry 256
10. Static MAC forwarding entry 256
11. MAC filtering entry 256
12. Cluster member 24
13. Management IP address 64
14. IGMP MVR entry 256
15. IGMP Filtering profile 256
16. Syslog server entry 4

Change History:

V3.70(All.0) (07/31/2006)

Firmware Upgrade:

The ES-2024PWR uses FTP to upgrade firmware in run-time through its built-in FTP server. You can use any FTP client (for example, [ftp.exe](#) in Windows) to upgrade ES-2024PWR. The upgrade procedure is as follows:

Upgrade ES-2024PWR FW:

```
C:\> ftp <ES-2024PWR IP address>
User : admin
Password: 1234
230 Logged in
ftp> put 370AII0c0.bin ras
ftp> bye
```

Where

- User name : the management user name, admin by default
- Password : the management password, 1234 by default
- 370AII0c0.bin : the name of firmware file you want to upgrade
- ras : the internal firmware name in ES-2024PWR

Configuration Upgrade:

The ES-2024PWR uses FTP to upgrade firmware in run-time through its built-in FTP server. You can use any FTP client (for example, [ftp.exe](#) in Windows) to upgrade ES-2024PWR. The upgrade procedure is as follows:

Upgrade ES-2024PWR configuration:

```
C:\> ftp <ES-2024PWR IP address>
User : admin
Password: 1234
230 Logged in
ftp> put 370AII0c0.rom rom-0
ftp> bye
```

Where

- User name : the management user name, admin by default
- Password : the management password, 1234 by default
- 370AII0c0.rom : the name of configuration file you want to upgrade
- rom-0 : the internal configuration name in ES-2024PWR