

YXEL's Omni 128L is a flexible, simple, easy

and economic solution for IDSL concentrator as the client side solution. This IDSL Modem can be used as long range transmission, campus environment, point-to-point connection. The Omni 128L can support 64K/128K symmetric and synchronous transmission, which is ideal IDSL CPE solution for ZyXEL Prestige 1600 IDSL concentrator. It also works with standard U loop ISDN repeaters to extend the range to 18,000 feet (11km) from the central office.

IDSL Compliance

- Symmetrical and synchronous data transmission 64K or 128K configured by the IDSL server
- Auto configured as 64K or 128K by ZyXEL Prestige 1600 IDSL concentrator
- Maximum Transmission distance 18,000 feet
- 2B1Q line modulation for level line code
- Transparent U loop ISDN repeater
- Manually rate adaptation configuration
- Tool-free installation

IDSL Network Compatibility

• Europe and Asia:DSS1,1TR6, INS-NET 64, Taiwan DGT

Protocol Support and Compression

- PPP Multilink Protocol supported in both call-mode and answer-mode for compatibility with ISDN devices form other vendors at spees of up to 128Kbps
- Flash EPROM for easy firmware upgrades







ISO 9001 Certified



Specifications are subject to change without notice.

All trademarks are the property of their respective owners.

International: Nor ZyXEL Communications Corp. ZyX

Tel: 886-3-5783942 Fax: 886-3-5782439 E-mail: sales@zyxel.com.tw support@zyxel.com.tw Web: http://www.zyxel.com

North America:

ZyXEL Communications, Inc. Tel: 714-632-0882 Fax: 714-632-0858 E-mail: sales@zyxel.com

support@zxyel.com Web: http://www.zyxel.com

Scandinavia:

ZyXEL Communications A/S Tel: 45-3955-0700 Fax: 45-3955-0707 E-mail: sales@zyxel.dk support@zyxel.dk

Web:http://www.zyxel.dk

Germany: ZvXEL Deutschland GmbH.

Tel: +49-2405-6909-0 Fax: +49-2405-6909-99 E-mail: sales@zyxel.de support@zyxel.de Web: http://www.zyxel.de

Austria: ZyXEL Communications Services GmbH.

Tel: +43-1-4948677-0 Fax: +43-1-4948678 E-mail: sales@zyxel.at support@zyxel.at Web: http://www.zyxel.at

Diagnostics Capabilities

- The IDSL modem can perform self-diagnostic tests. These tests check the integrity of the following circuitry:
 - FLASH memory
 - IDSL circuitry
 - RAM

DTE Interface

 Need a 16650 based multiple speed I/O card installed in PC for 128K connection speed

Physical Interface

- One RS-232 interface for local configuration
- One RJ-45 port for connecting IDSL concentrator
- Dimensions: 9W x 7.5D x 2.2H in. (23W x 19D x 5.6H cm)
- Weight: 2.1 lbs. (0.95 Kg)

Operating Environment

Temperature: 0 C to 40 CHumidity: 5% to 95 %

Two year warranty