

RBGL: R interface to boost graph library

VJ Carey `stvjc@channing.harvard.edu`

August 24, 2004

Summary. An interface from R to the Boost Graph Library (BGL, an alternative to STL programming for mathematical graph objects) is described.
This 2003 update employs the graph class of Bioconductor.

Contents

1	Working with the Bioconductor graph class	1
2	Algorithms supported by RBGL	3
2.1	Topological sort	3
2.2	Kruskal's minimum spanning tree	3
2.3	Depth first search	4
2.4	Breadth first search	5
2.5	Dijkstra's shortest paths	6
2.6	Connected components	8
2.7	Strongly connected components	9
2.8	Edge connectivity and minimum disconnecting set	9

1 Working with the Bioconductor graph class

An example object representing file dependencies is included, as shown in Figure 1.

```
> library(RBGL)
> data(FileDep)
> print(FileDep)
```

```
A graph with directed edges
Number of Nodes = 15
Number of Edges = 19
```




Figure 1: File dependency digraph example from Boost library.

2 Algorithms supported by RBGL

2.1 Topological sort

The `tsort` function will return the indices of vertices in topological sort order:

```
> ts <- tsort(FileDep)

Loading required package: Biobase
Welcome to Bioconductor
  Vignettes contain introductory material. To view,
  simply type: openVignette()
  For details on reading vignettes, see
  the openVignette help page.

> print(nodes(FileDep)[ts + 1])

[1] "zow_h"        "boz_h"        "zig_cpp"      "zig_o"        "dax_h"
[6] "yow_h"        "zag_cpp"      "zag_o"        "bar_cpp"      "bar_o"
[11] "foo_cpp"      "foo_o"        "libfoobar_a" "libzigzag_a" "killerapp"
```

Note that if the input graph is not a DAG, BGL `topological_sort` will check this and throw 'not a dag'. This is crudely captured in the interface (a message is written to the console and zeroes are returned).

```
#FD2 <- FileDep
# now introduce a cycle
#FD2@edgeL[["bar_cpp"]]$edges <- c(8,1)
#tsort(FD2)
```

2.2 Kruskal's minimum spanning tree

Function `mstree.kruskal` just returns a list of edges, weights and nodes determining the minimum spanning tree (MST) by Kruskal's algorithm.

```
> km <- fromGXL(file(system.file("GXL/kmstEx.gxl", package = "graph")))
> print(mstree.kruskal(km))

$edgeList
 [,1] [,2] [,3] [,4]
[1,]    1    4    5    2
[2,]    3    5    1    4

$weights
 [,1] [,2] [,3] [,4]
```




Figure 2: Kruskal MST example from Boost library.

```
[1,]      1      1      1      1
```

```
$nodes
[1] "A" "B" "C" "D" "E"
```

2.3 Depth first search

The `dfs` function returns a list of node indices by discovery and finish order.

```
> df <- fromGXL(file(system.file("XML/dfsex.gxl", package = "RBGL")))
> print(o <- dfs(df))

$discovered
[1] 1 2 5 4 3 6
```




Figure 3: DFS example from Boost library.

```
$finish
[1] 4 5 2 1 6 3
```

Here is the list of nodes in DFS discovery order.

```
> print(nodes(df)[o$discovered])
[1] "u" "v" "y" "x" "w" "z"
```

2.4 Breadth first search

The `bfs` function returns a vector of node indices for a breadth-first search (BFS) starting at the node indexed by `init.node`.

```

> bf <- fromGXL(file(system.file("XML/bfsex.gxl", package = "RBGL")))
> bf@edgemode <- "undirected"
> print(o <- bfs(bf, nodes(bf)[2]))

[1] 1 2 3 4 5 6 7 8

```

The nodes in BFS order starting with the second node are

```

> print(nodes(bf)[o])

[1] "r" "s" "t" "u" "v" "w" "x" "y"

```

2.5 Dijkstra's shortest paths

```

> dd <- fromGXL(file(system.file("XML/dijkex.gxl", package = "RBGL")))
> print(dijkstra.sp(dd))

```

```

$distances
A B C D E
0 6 1 4 5

```

```

$penult
A B C D E
1 5 1 3 4

```

```

$start
A
1

```

```

> ospf <- fromGXL(file(system.file("XML/ospf.gxl", package = "RBGL")))

```

```

> dijkstra.sp(ospf, nodes(ospf)[6])

```

```

$distances
RT1 RT2 RT3 RT4 RT5 RT6 RT7 RT8 RT9 RT10 RT11 RT12 N1 N2 N3 N4
  7   7   6   7   6   0   8   8   11  7   10  11  10  10  7   8
N6  N7  N8  N9  N10 N11 N12 N13 N14 N15 H1
  8   12  10  11  13  14  10  14  14  17  21

```

```

$penult
RT1 RT2 RT3 RT4 RT5 RT6 RT7 RT8 RT9 RT10 RT11 RT12 N1 N2 N3 N4
  15  15   6   15   6   6   17   17   20   6   19   20   1   2   3   3
N6  N7  N8  N9  N10 N11 N12 N13 N14 N15 H1

```




Figure 4: Network example from BGL.

```

10     8     10    11    12     9     7     5     5     7    12

$start
RT6
  6

> sp.between(ospf, "RT6", "RT1")

$"RT6:RT1"
$"RT6:RT1$path
[1] "RT6" "RT3" "N3"   "RT1"

$"RT6:RT1">$length
[1] 7

$"RT6:RT1">$pweights
RT6->RT3  RT3->N3  N3->RT1
      6        1        0

> dd <- fromGXL(file(system.file("XML/dijkex.gxl", package = "RBGL")))
> print(dijkstra.sp(dd))

$distances
A B C D E
0 6 1 4 5

$penult
A B C D E
1 5 1 3 4

$start
A
1

```

2.6 Connected components

```

> km <- fromGXL(file(system.file("GXL/kmstEx.gxl", package = "graph")))
> km@nodes <- c(km@nodes, "F", "G", "H")
> km@edgeL$F <- list(edges = numeric(0))
> km@edgeL$G <- list(edges = 8, weights = 1)
> km@edgeL$H <- list(edges = 7, weights = 1)
> km@edgemode <- "undirected"
> if (length(agrep("solaris", version[["platform"]])) == 0) print(connectedComp(ugraph)

```

```

$"1"
[1] "A" "B" "C" "D" "E"

$"2"
[1] "F"

$"3"
[1] "G" "H"

```

2.7 Strongly connected components

```

> km <- fromGXL(file(system.file("GXL/kmstEx.gxl", package = "graph")))
> km@nodes <- c(km@nodes, "F", "G", "H")
> km@edgeL$F <- list(edges = numeric(0))
> km@edgeL$G <- list(edges = 8, weights = 1)
> km@edgeL$H <- list(edges = 7, weights = 1)
> km@edgemode <- "directed"
> print(strongComp(km))

$"1"
[1] "A" "B" "C" "D" "E"

$"2"
[1] "F"

$"3"
[1] "G" "H"

```

2.8 Edge connectivity and minimum disconnecting set

```

> coex <- fromGXL(file(system.file("XML/conn.gxl", package = "RBGL")))
> dcoex <- coex
> dcoex@edgemode <- "directed"
> udcoex <- ugraph(dcoex)

> if (length(agrep("solaris", version[["platform"]])) == 0) print(edgeConnectivity(co
$connectivity
[1] 2

$minDisconSet
$minDisconSet[[1]]

```




Figure 5: Edge connectivity example.

```
[1] "D" "E"
```

```
$minDisconSet[[2]]  
[1] "D" "H"
```